

G 40P-VdS, G 40J, GS 40P, GS 40J

- ◆ 24V- electrically operated spindle actuator, in anodized aluminium enclosure.
Push rod: anodized aluminum Ø22 (G40P/G40J) or steel Ø22 (GS40P/GS40J)
- ◆ Rated current: 4,0A
- ◆ VdS approval G 502006
- ◆ Ambient temperature range -5 to +75°C; to VdS 2580 for 2hrs up to +110°C
- ◆ Dimensions: see data sheet
- ◆ Disconnection at either end position by integrated limit switches
- ◆ Electronic “emergency stop” on overload
- ◆ Protection to DIN EN 60529: IP54 (for use in dry rooms)
- ◆ Light grey silicone supply cable brought out at upper end, length approx. 2,5m, temperature range -50 to +180°C (to DIN VDE 0282)
- ◆ Continuous adjustability in mounting ensured by sliding blocks and bearing pins LB12-SL13-M5x16 (included)
- ◆ Including eyebolt M8 Ø8mm

Types:

Standard stroke: 350, 550 or 750mm,
For special stroke, please inquire.

Options: (see Data sheet)

Other cable length: specify full meters

Eyebolt: M8 Ø6mm or Ø10mm

E: Additional switches integrated for indication of both end positions (potential-free NC contacts, 24V- / 1A).

RAL: Actuator enclosure painted in a RAL colour

KS / KM: : Supply cable exit is at side of lower end of actuator.

For more special versions please inquire

